

Holden V8 & SB Chev HYD Roller Profiles

Master Number	Advertised Duration @.006"		Duration @ .050"		Duration @ .200"		Lobe Sep	Cam Lift	
	IN	EX	IN	EX	IN	EX		IN	EX
487	264	271	207	215	110	118	117	0.275	0.285
49908	264	266	207	213	121	126	113	0.311	0.311
49912	266	270	208	213	123	128	112	0.333	0.332
489	270	276	208	213	114	118	112	0.293	0.294
480	269	279	210	220	131	138	116	0.329	0.329
477	274	274	212	212	120	120	114	0.294	0.294
49915	267	267	213	213	138	138	112	0.353	0.347
467	282	293	217	229	130	141	112	0.316	0.332
49925	276	276	217	217	133	133	112	0.325	0.325
49920	275	275	220	220	141	141	112	0.341	0.341
49919	275	287	220	228	141	149	114	0.341	0.348
49928	278	286	222	230	140	148	112	0.339"	0.352"
49907	280	284	223	227	142	146	111	0.353	0.353
49903	286	288	230	233	148	152	110	0.351	0.358
49906	285	285	231	231	150	150	113	0.348	0.351
49901	288	290	234	237	154	157	110	0.355	0.356
49934	290	298	235	242	154	157	112	0.360"	0.365"
49923	296	305	237	246	160	164	110	0.375	0.374
49943	306	320	247	260	165	177	111	0.370"	0.368"
481	302	307	248	254	171	178	110	0.374	0.386